



P.O. BOX 930220
 VERONA, WI 53593-0220
 (608) 845-9700 / Fax (608) 845-7070
 www.clearybuilding.com



“CLEARLY” CLEARLY TEST

Check the features, give them the test, and add it up! Add +1 for Yes and -1 for No

FABRAL STEEL STRENGTH

- ♣ Fabral uses only 29 gauge, 80,000 PSI bare steel with a minimum .015 thickness before paint to assure you of the thickest, strongest panel in the industry (UP TO 50% STRONGER THAN SOME COMPETITORS 26 gauge, 40,000 PSI STEEL)
- ♣ Trapezoidal Rib Configuration, Major Ribs 9” on center for added strength (compared to 12” on center of many of our competitors)
- ♣ Specially designed 3/8” nailing crown to prevent leaks
- ♣ Load capacity of **236 PSF** with purlins 24” on center
- ♣ ¾” High Ribs, more bends equals Greater Strength

	Clearly Yes	Other No
1		
1		
1		
1		
1		

FABRAL COATING SYSTEM

- ♣ Galvanization (2 layers): Grandrib 3 Plus has up to 1.0 oz. of zinc protection as compared to competitors’ G60 or G90 products, resulting in up to 67% corrosion protection.
- ♣ ENDURACOTE paint system (for much higher **fade & scratch resistance** than conventional paint systems)
- ♣ 22 colors to choose from

1		
1		
1		

FABRAL GRAND RIB III PLUS STEEL WARRANTY (INDUSTRY LEADER)

- ♣ LIFETIME – *Film Integrity* – Sidewall Panels / Craziing and Peeling
- ♣ LIFETIME – *Film Integrity* – Roof Panels / Craziing and Peeling
- ♣ 35 Year Warranty – Roof and Sidewall Panels / Chalking and Fading
- ♣ 30 Year Warranty – Sidewall Panels / Red Rust Corrosion
- ♣ 25 Year Warranty – Roof Panels / Red Rust Corrosion

1		
1		
1		
1		
1		

CLEARY COLUMNS

- ♣ 3 ply laminated #1 SYP CCA treated
- ♣ Continuous non-spliced lumber (**2.4 times stronger** than spliced columns used by many competitors).
- ♣ Treated from footing to eaveline on sidewall columns
- ♣ **50 year** decay/insect warranty

1		
1		
1		
1		

OTHER ADVANTAGES

- ♣ Energy Miser Insulation package
- ♣ Cleary employed, trained, and insured construction crews
- ♣ Multiple United States locations for prompt sales and service

1		
1		
1		
TOTALS	20	

Construction details and material specifications are subject to change without prior notice or obligation

042307



built with pride before the shamrock is applied

